

1. Identification

Product identifier Steel Deck (Painted and Unpainted)

Other means of identification Not available.

Recommended use Roof deck, sub floor deck.

Recommended restrictions None known.

Manufacturer / Importer / Supplier / Distributor information

Manufacturer/Supplier New Millennium Building Systems
6115 County Road 42, Butler, IN 46721
Telephone: 260-868-6000

100 Diuguids Lane, Salem, VA 24153
540-389-0211

1992 NW Bascom Norris Drive, Lake City, FL 32055
Telephone: 386-466-1300

3565 US Highway 32 North, Hope, AR 71801
Telephone: 870-722-4100

Contact Person Safety Department
Emergency (800)-424-9300

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.

Signal word None.

Hazard statement None.

Precautionary statement

Prevention Avoid creating dust.

Response Wash skin with soap and water.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise classified (HNOC) Not classified.

Supplemental information

Hazard statement In its manufactured and shipped state, this product is considered non-hazardous. Processing may generate hazardous fumes and dusts. Welding, cutting and metalizing can generate ozone. Ozone can cause irritation of eyes, nose and respiratory tract.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Iron	7439-89-6	>90
Manganese	7439-96-5	0-2
Chromium	7440-47-3	0-1
Coating(s)	-	< 1
Silicon	7440-21-3	0-1
Nickel	7440-02-0	0-0.4

Vanadium	7440-62-2	0-0.2
Iron oxide**	1309-37-1	0
Vanadium pentoxide**	1314-62-1	0

The product is an alloy. The alloy surface is coated. May liberate hazardous oxides such as iron oxides and vanadium pentoxide at temperatures above the melting point.

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.
Coating may contain chromium in the range of 1.5-2 mg of chromium/sq foot or 10-15 mg of chromium/sq foot depending on the treatment.
**Iron oxide and vanadium pentoxide are formed at temperatures above the melting point.

4. First-aid measures

Inhalation In case of inhalation of dusts or fumes from heated product: Move into fresh air and keep at rest. Get medical attention if symptoms persist. If breathing is difficult, give oxygen. If breathing stops, provide artificial respiration.

Skin contact Wash skin with soap and water. In case of burns with hot metal, rinse with plenty of cold water. If burns are severe, consult a physician. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. Get medical attention promptly if symptoms persist or occur after washing.

Ingestion Solid steel: Not applicable. Dust: Get medical attention if any discomfort continues.

Most important symptoms/effects, acute and delayed Exposed individuals may experience eye tearing, redness, and discomfort. May dry the skin leading to discomfort and dermatitis. Prolonged contact may cause redness, irritation and cracking. High concentrations of freshly formed fumes/dusts of metal oxides can produce symptoms of metal fume fever. Typical symptoms last 12 to 48 hours and are characterized by metallic taste in the mouth, dryness, and irritation of the throat, followed by weakness, muscle pain, fever, and chills.

5. Fire-fighting measures

Suitable extinguishing media No unusual fire or explosion hazards noted. Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media None known.

Specific hazards arising from the chemical By heating and fire, toxic vapors/gases may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Cold solid metal: No special precautions are necessary beyond normal good hygiene practices. See Section 8 of the MSDS for additional personal protection advice when handling this product. Hot metal: Avoid contact with hot material. Wear protective clothing as described in Section 8 of this safety data sheet.

Methods and materials for containment and cleaning up In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Collect for recycling.

Environmental precautions No specific precautions.

7. Handling and storage

Precautions for safe handling Avoid contact with sharp edges and hot surfaces. Use appropriate gloves and tools to ensure safe handling. Use work methods which minimize dust/fume production. Observe safety measures suited to the coating(s) when handling, cutting or melting. Do not breathe fumes and dusts. Follow the recommendations in ANSI Z49.1, Safety in welding and cutting (ANSI=American National Standard Institute). Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in a dry place. Store away from: Oxidizing agents. Acids.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	PEL	1 mg/m3	
Iron oxide** (CAS 1309-37-1)	PEL	10 mg/m3	Fume.
Manganese (CAS 7439-96-5)	Ceiling	5 mg/m3	Fume.
Nickel (CAS 7440-02-0)	PEL	1 mg/m3	
Silicon (CAS 7440-21-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Vanadium pentoxide** (CAS 1314-62-1)	Ceiling	0.5 mg/m3	Respirable dust.
		0.1 mg/m3	Fume.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	0.5 mg/m3	
Iron oxide** (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
Manganese (CAS 7439-96-5)	TWA	0.1 mg/m3	Inhalable fraction.
		0.02 mg/m3	Respirable fraction.
Nickel (CAS 7440-02-0)	TWA	1.5 mg/m3	Inhalable fraction.
Vanadium pentoxide** (CAS 1314-62-1)	TWA	0.05 mg/m3	Inhalable fraction.

US NIOSH Pocket Guide to Chemical Hazards: Ceiling Limit Value and Time Period (if specified)

Components	Type	Value	Form
Vanadium pentoxide** (CAS 1314-62-1)	Ceiling	0.05 mg/m3	Fume.
		0.05 mg/m3	Dust.

US NIOSH Pocket Guide to Chemical Hazards: Recommended exposure limit (REL)

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	0.5 mg/m3	
Iron oxide** (CAS 1309-37-1)	TWA	5 mg/m3	Dust and fume.
Manganese (CAS 7439-96-5)	TWA	1 mg/m3	Fume.
Nickel (CAS 7440-02-0)	TWA	0.015 mg/m3	
Silicon (CAS 7440-21-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Vanadium (CAS 7440-62-2)	TWA	1 mg/m3	

US NIOSH Pocket Guide to Chemical Hazards: Short Term Exposure Limit (STEL)

Components	Type	Value	Form
Manganese (CAS 7439-96-5)	STEL	3 mg/m3	Fume.
Vanadium (CAS 7440-62-2)	STEL	3 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

**Iron oxide and vanadium pentoxide are formed at temperatures above the melting point.

Appropriate engineering controls

Adequate ventilation should be provided so that exposure limits are not exceeded. Use local exhaust when welding, burning, sawing, brazing, grinding or machining to prevent excessive dust or fume exposure.

Individual protection measures, such as personal protective equipment

Eye/face protection

Use of safety glasses or goggles is required for welding, burning, sawing, brazing, grinding or machining operations. In addition to safety glasses or goggles, a welding helmet with appropriate shaded shield is required during welding, burning, or brazing. A face shield is recommended, in addition to safety glasses or goggles, during sawing, grinding, or machining.

Skin protection

Hand protection

Wear protective gloves.

Other

Wear suitable protective clothing.

Respiratory protection	Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.
Thermal hazards	When material is heated, wear gloves to protect against thermal burns. Thermally protective apron and long sleeves are recommended when volume of hot material is significant.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance	Solid.
Physical state	Solid.
Form	Solid.
Color	White/Gray (painted) Metallic gray (unpainted).
Odor	None.
Odor threshold	Not applicable.
pH	Not applicable.
Melting point/freezing point	2750 °F (1510 °C) / Not applicable.
Initial boiling point and boiling range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not applicable.
Flammability limit - upper (%)	Not applicable.
Explosive limit - lower (%)	Not applicable.
Explosive limit - upper (%)	Not applicable.
Vapor pressure	Not applicable.
Vapor density	Not applicable.
Relative density	7 - 8
Solubility(ies)	Not applicable.
Partition coefficient (n-octanol/water)	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not applicable.
Viscosity	Not applicable.

10. Stability and reactivity

Reactivity	Stable at normal conditions.
Chemical stability	This product is stable under expected conditions of use.
Possibility of hazardous reactions	Will not occur.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong acids. Oxidizing agents.
Hazardous decomposition products	At elevated temperatures: Acrid fumes. Metal oxides. Metallic fumes. Organic fumes. Strong Acid Contact: Hydrogen. Inorganic compounds.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Solid steel: Not relevant, due to the form of the product. However, ingestion of dusts generated during working operations may cause nausea and vomiting.
Inhalation	No inhalation hazard under normal conditions. Welding, burning, sawing, brazing, grinding or machining operations may generate fumes and dusts of metal oxides.

Skin contact	Under normal conditions of intended use, this material does not pose a risk to health. Dust may irritate skin. Skin contact may aggravate an existing dermatitis. Contact with hot material can cause thermal burns which may result in permanent damage.	
Eye contact	Under normal conditions of intended use, this material does not pose a risk to health. Contact with hot material can cause thermal burns which may result in permanent damage. Grinding and sanding this product may generate dust. Dust may irritate the eyes.	
Symptoms related to the physical, chemical and toxicological characteristics	Exposed individuals may experience eye tearing, redness, and discomfort. May dry the skin leading to discomfort and dermatitis. Prolonged contact may cause redness, irritation and cracking. High concentrations of freshly formed fumes/dusts of metal oxides can produce symptoms of metal fume fever. Typical symptoms last 12 to 48 hours and are characterized by metallic taste in the mouth, dryness, and irritation of the throat, followed by weakness, muscle pain, fever, and chills.	
Information on toxicological effects		
Acute toxicity	Processing may generate hazardous fumes and dusts. High concentrations of dust may irritate throat and respiratory system and cause coughing. Welding, cutting and metalizing can generate ozone. Ozone can cause irritation of eyes, nose and respiratory tract.	
Components	Species	Test Results
Iron (CAS 7439-89-6)		
Acute		
<i>Inhalation</i>		
LC50	Rat	250 mg/m ³ , 6 Hours, (Carbonyl iron)
<i>Oral</i>		
LD50	Rat	7500 mg/kg
Silicon (CAS 7440-21-3)		
Acute		
<i>Oral</i>		
LD50	Rat	3160 mg/kg
Skin corrosion/irritation	Dust may irritate skin.	
Serious eye damage/eye irritation	Dust may irritate the eyes.	
Respiratory sensitization	Not relevant, due to the form of the product. Contains nickel: May cause allergy or asthma symptoms or breathing difficulties if inhaled. This ingredient is bound within the product and release is not expected under normal condition.	
Skin sensitization	Contains nickel: May cause an allergic skin reaction.	
Germ cell mutagenicity	Not relevant, due to the form of the product. May liberate hazardous vanadium pentoxide at temperatures above the melting point. Vanadium pentoxide is classified as suspected of causing genetic defects. This ingredient is bound within the product and release is not expected under normal condition.	
Carcinogenicity	Not relevant, due to the form of the product. May liberate hazardous oxides such as iron oxides and vanadium pentoxide at temperatures above the melting point. Inhalation of high concentrations of iron oxide may possibly enhance the risk of lung cancer development in workers exposed to pulmonary carcinogens. A residual chrome VI compound from the surface coating is water soluble and is carcinogenic. Chromium VI compounds are regarded as human carcinogens by IARC, NTP, OSHA and ACGIH. Vanadium pentoxide is classified as possibly carcinogenic to humans (Group 2B) by IARC. This ingredient is bound within the product and release is not expected under normal condition.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Chromium (CAS 7440-47-3)	3 Not classifiable as to carcinogenicity to humans.	
Iron oxide** (CAS 1309-37-1)	3 Not classifiable as to carcinogenicity to humans.	
Nickel (CAS 7440-02-0)	2B Possibly carcinogenic to humans.	
Vanadium pentoxide** (CAS 1314-62-1)	2B Possibly carcinogenic to humans.	
NTP Report on Carcinogens		
Nickel (CAS 7440-02-0)	Known To Be Human Carcinogen. Reasonably Anticipated to be a Human Carcinogen.	
Reproductive toxicity	Not relevant, due to the form of the product. May liberate hazardous vanadium pentoxide at temperatures above the melting point. Vanadium pentoxide is classified as suspected of damaging fertility or the unborn child. This ingredient is bound within the product and release is not expected under normal condition.	
Specific target organ toxicity - single exposure	No data available.	
Specific target organ toxicity - repeated exposure	Not relevant, due to the form of the product. Contains Manganese: Causes damage to organs (lung) through prolonged or repeated exposure by inhalation. This ingredient is bound within the product and release is not expected under normal condition.	

Aspiration hazard	Due to the physical form of the product it is not an aspiration hazard.
Chronic effects	Frequent inhalation of dust over a long period of time increases the risk of developing asthma, chronic lung diseases, and skin irritation. Chronic inhalation of high concentrations of iron oxide fumes or dust may lead to benign pneumoconiosis (siderosis). Exposure to manganese fume/dust can affect the central nervous system (apathy, drowsiness, weakness and other chronic symptoms such as postural tremors). Pre-existing skin and respiratory conditions including dermatitis, asthma and chronic lung disease might be aggravated by exposure. The ingredients of the alloy are bound within the product and release is not expected under normal conditions.

12. Ecological information

Ecotoxicity The environmental hazard of the product is considered to be limited.

Components	Species	Test Results
Iron (CAS 7439-89-6) Aquatic		
Fish	LC50 Channel catfish (<i>Ictalurus punctatus</i>)	> 500 mg/l, 96 hours
Nickel (CAS 7440-02-0) Aquatic		
Fish	LC50 Fathead minnow (<i>Pimephales promelas</i>)	2.916 mg/l, 96 hours
Vanadium pentoxide** (CAS 1314-62-1) Aquatic		
Fish	LC50 Tigerfish, crescent perch (<i>Therapon jarbua</i>)	0.62 mg/l, 96 hours

Persistence and degradability	No data available.
Bioaccumulative potential	No data available on bioaccumulation.
Mobility in soil	Not relevant, due to the form of the product.
Other adverse effects	None known.

13. Disposal considerations

Disposal instructions	Dispose waste and residues in accordance with applicable federal, state, and local regulations.
Hazardous waste code	Not regulated.
Waste from residues / unused products	Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal. Recover and recycle, if practical.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT
Not regulated as a hazardous material by DOT.

IATA
Not regulated as a dangerous good.

IMDG
Not regulated as a dangerous good.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations Under some use conditions, this material may be considered to be hazardous in accordance with OSHA 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Chromium (CAS 7440-47-3)	LISTED
Manganese (CAS 7439-96-5)	LISTED
Nickel (CAS 7440-02-0)	LISTED
Vanadium pentoxide** (CAS 1314-62-1)	LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Manganese	7439-96-5	0-2
Chromium	7440-47-3	0-1
Nickel	7440-02-0	0-0.4

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Chromium (CAS 7440-47-3)
Manganese (CAS 7439-96-5)
Nickel (CAS 7440-02-0)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

US state regulations WARNING: This product contains chemical(s) known to the State of California to cause cancer.

US. Massachusetts RTK - Substance List

Chromium (CAS 7440-47-3)
Iron oxide** (CAS 1309-37-1)
Manganese (CAS 7439-96-5)
Nickel (CAS 7440-02-0)
Silicon (CAS 7440-21-3)
Vanadium (CAS 7440-62-2)
Vanadium pentoxide** (CAS 1314-62-1)

US. New Jersey Worker and Community Right-to-Know Act

Chromium (CAS 7440-47-3) 500 lbs
Manganese (CAS 7439-96-5) 500 lbs
Nickel (CAS 7440-02-0) 500 lbs
Vanadium (CAS 7440-62-2) 500 lbs
Vanadium pentoxide** (CAS 1314-62-1) 100 lbs

US. Pennsylvania RTK - Hazardous Substances

Chromium (CAS 7440-47-3)
Iron oxide** (CAS 1309-37-1)
Manganese (CAS 7439-96-5)
Nickel (CAS 7440-02-0)
Silicon (CAS 7440-21-3)
Vanadium (CAS 7440-62-2)
Vanadium pentoxide** (CAS 1314-62-1)

US. Rhode Island RTK

Chromium (CAS 7440-47-3)
Manganese (CAS 7439-96-5)
Nickel (CAS 7440-02-0)
Vanadium (CAS 7440-62-2)
Vanadium pentoxide** (CAS 1314-62-1)

US. California Proposition 65

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Nickel (CAS 7440-02-0)
Vanadium pentoxide** (CAS 1314-62-1)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).


16. Other information, including date of preparation or last revision

Issue date 23-August-2013

Revision date -

Version # 01

NFPA Ratings



Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment. MSDS's for specific coatings are available upon request.